RFGREEN® Stainless Steel Tape - TECHNICAL DATA 2024/06

CPC-GSS25

Grounding tape for stainless steel gauzes and fleeces, in-wall or in dry wall constructions.

Application

The stainless steel gauze elements or fleece elements are attached / glued with 5-10 cm overlap. To interconnect all elements, the tape is screwed together across over all elements together with the underground as often as possible, especially on the overlapping locations. Before using, the tape has to be degreased with a piece of cloth.

- Length 25 m, width 12 mm, thickness 0,8 mm, hole spacing 14.5 mm, hole size 5 mm
- Corrosion-resistant
- In environment friendly carton packaging

FOR PROFESSIONAL USE ONLY - SOLO PARA USO PROFESIONALY

Specifications Overview

- Length: 25 meters (82 feet)
- Width: 12 mm (0.47 inches)
- Thickness: 0.8 mm
- Material: Stainless steel
- Hole Spacing: 14.5 mm
- Hole Size: 5 mm
- Application: Grounding for stainless steel gauzes and fleeces in wall or dry wall constructions
- Usage: Attach/glue elements with 5-10 cm overlap, screw together across elements

RELATED PRODUCTS

CPC-GS
Grounding Plates

CPC-GL
Grounding Cables

CPC-GSX
Grounding Straps